

SPECIFICATIONS

# 1166 / 1266

Wireless Scanners



1166

1266

	1166	1266	
<b>RF communication</b>	Module	BT Class 2 compliance	
	Coverage (line of sight)	100 m / 328 feet	
	Standard profile	SPP, HID or through 3666 base	
<b>Performance</b>	Optical sensor	3648 pixels	Laser
	Light source	Red LED 630 nm	Visible laser diode at 650±15 nm
	Resolution	4 mil	3 mil
	Depth of field <small>depends on barcode resolution</small>	2 to 33 cm / 0.8 to 13 in.	1 to 63 cm / 0.4 to 24.8 in.
	Scanning angle	Pitch ±70° Skew ±70°	
	PCS	Minimum 45%	
	Scan rate	100 scans/second	
	Interfaces supported	RS232 / Keyboard wedge / USB HID	
	Barcodes supported	Codabar, Code 39, Code 93, Code 128, GS1 Databar (RSS) Industrial 2 of 5, Interleave 2 of 5, Matrix 2 of 5, MSI, Pharmacodes, Plessey, Telepen, UPC/EAN/GS1-128, and more	
	Programmable features	Data editing, interface selection, symbology configuration	
	Language support	US and UK English, French, Italian, Belgian, Norwegian, Swedish, Spanish, Portuguese, German	
<b>Physical</b>	Weight including battery	200 g / 7.1 oz.	210 g / 7.4 oz.
	Color	Dark grey	
	Switch	Micro switch	
<b>Electrical</b>	Voltage	DC 5V ±5% (with adapter) / 3.7V 700 mAh Li-ion battery	
	Power consumption <small>Standby / Scanning / Maximum</small>	12 mA / 170 mA / 250 mA	12 mA / 85 mA / 150 mA
<b>User environment</b>	Temperature	Operating: 0° to 50°C / 32° to 122°F	Storage: -20° to 60°C / -4° to 140°F
	Humidity Non-condensing	Operating: 10% to 90%	Storage: 5% to 95%
	Impact resistance	Withstands multiple 1.2 m / 4 ft. drops onto concrete	
	Electrostatic discharge	Conforms to ±15 kV air discharge and ±8 kV contact discharge	
	EMC regulation	BSMI, CE, C-Tick, FCC, MIC, VCCI	
<b>Configuration</b>	Setup options include Windows®-based ScanMaster software (included), by direct connection or printing out barcode settings		
<b>Accessories</b>	Charging cradle and charging/communication cradle		
<b>Warranty</b>	3 year	3 year (laser engine 1 year)	

**Charging/Communication Cradle**  
 Simultaneously communicates with up to seven 1166/1266 scanners



©2009 CipherLab Co., Ltd. All specifications are subject to change without notice. All rights reserved. All brand, product and service, and trademark names are the property of their registered owners.



**HEADQUARTERS**  
 CipherLab Co., Ltd.  
 12F, 333 Dunhua S. Rd., Sec. 2  
 Taipei, Taiwan 10669  
 Tel +886 2 8647 1166  
 Fax +886 2 8732 3300  
 www.cipherlab.com

**CipherLab China**  
 Suite 1305, 1065A, Jaojiabang Rd.  
 Xuhui District, Shanghai,  
 China 200030  
 Tel +86 21 3368 0288  
 Fax +86 21 3368 0286

**CipherLab USA**  
 2552 Summit Avenue  
 Plano, Texas USA 75074  
 Tel +1 469 241 9779  
 Toll Free 888 300 9779  
 Fax +1 469 241 0697

**CipherLab Central Europe**  
 Willicher Damm 143-145  
 41066 Mönchengladbach  
 Germany  
 Tel +49 2161 56230 0  
 Fax +49 2161 56230 22